


BEST AVAILABLE COPY

(19)

Generated Document.

(11) Publication number: **04005036 A****PATENT ABSTRACTS OF JAPAN**(21) Application number: **02105470**(51) Int. Cl.: **B32B 7/06 B32B 7/02 B32B 27/30**(22) Application date: **23.04.90**

(30) Priority:

(43) Date of application
publication: **09.01.92**(84) Designated contracting
states:(71) Applicant: **RIKEN VINYL KOGYO KK**(72) Inventor: **DAIDOUKOU NOBUO
IWAMOTO YOSHIAKI**

(74) Representative:

**(54) COMPOSITE FILM ON
WHICH SUPPORTING FILM
IS ADHERED
TEMPORARILY**

(57) Abstract:

PURPOSE: To prevent a PVC film from occurrence of shrinkage and deformation while it is treated by coating or other treatment by temporarily adhering one face of polyvinyl chloride resin (PVC) film with a supporting film having heat resistance and dimensional stability such that it can be peeled off.

CONSTITUTION: A PVC film and a

BEST AVAILABLE COPY

supporting film are temporarily adhered together by heat adhesion under a proper heating and pressing condition to improve resistance to heating and tension and to obtain a treated film with small dimensional change even if the composite film is treated by printing, coating or in some cases, coating with a foamed layer. After the PVC film is treated, a PVC film with no dimensional change can be obtained by peeling off the supporting film. The resin which can be used as the supporting film are such a resin that has heat resistance, solvent resistance and dimensional stability and can be adhered temporarily with and easily peeled off from a polyvinyl chloride and the most preferred one is a polyester resin and especially preferred is a polyester resin consisting of terephthalic acid or isophthalic acid and ethylene glycol.

COPYRIGHT: (C)1992,JPO&Japio